

Hermetic light line



# IZAR-2EM



Type	Power	Supply	Luminous flux	Diffuser	Beam angle	Colour of light	Power factor	Dimensions L x W x H	Weight
	[W]	[V AC]	[lm]			[K]	[cosφ]	[mm]	[kg]
IZAR-2-EM-60-2400-D/M	20	220-240	2400	opal	100°	4000	>0,95	631x66x63	1,40
IZAR-2-EM-112-4800-D/M	40	220-240	4800	opal	100°	4000	>0,95	1151x66x63	2,20
IZAR-2-EM-112-6000-D/M	50	220-240	6000	opal	100°	4000	>0,95	1151x66x63	2,20
IZAR-2-EM-112-8400-D/M	70	220-240	8400	opal	100°	4000	>0,95	1151x66x63	2,20
IZAR-2-EM-140-9300-D/M	78	220-240	9400	opal	100°	4000	>0,95	1431x66x63	2,70
IZAR-2-EM-60-2600-D/T	20	220-240	2600	clear	100°	4000	>0,95	631x66x63	1,40
IZAR-2-EM-112-5100-D/T	40	220-240	5100	clear	100°	4000	>0,95	1151x66x63	2,20
IZAR-2-EM-112-6300-D/T	50	220-240	6350	clear	100°	4000	>0,95	1151x66x63	2,20
IZAR-2-EM-112-8900-D/T	70	220-240	8900	clear	100°	4000	>0,95	1151x66x63	2,20
IZAR-2-EM-140-9900-D/T	78	220-240	9900	clear	100°	4000	>0,95	1431x66x63	2,70
IZAR-2-EM-140-12100-D/T	78	220-240	12100	clear	100°	4000	>0,95	1431x66x63	2,70

Aesthetic and very efficient hermetic LED fixture in version with emergency module. Housing made of powder coated aluminium.

Opal or clear diffuser made of polycarbonate, pendant or surface mounted.

Mounting elements for pendant or surface mounted installation e.g. bracket FAST-I included.

Application: hermetic light fixtures IZAR - 2EM are intended to be used as the main lighting of facilities where is required the high ingress protection of fixtures. Operating in the emergency mode : fully charging accumulators batteries – 24h, operating in the emergency mode – 3h, luminous flux – approx. 700lm.

Standard: Ra≥80, colour of light 4000 K, non- dimmable driver , grey casing colour.

Options : Ra≥90, different colour of light, any body colour, DALI system/other.

